



EC-PC4UD55B-BC-PVC-XXX-GY-yy

Patch cord Cat.5e, 4 pairs, stranded wire (7*0.16mm), PVC, Grey, 10 or 5 pcs/bag

Ordering Table

P/N	Construction	Cat.	Length, m	QTY in group bag Transport box		Size, mm	Mass, kg
					QTY		
EC-PC4UD55B-BCU/UTP		5e	0,3	10	20	350x240x180	4
EC-PC4UD55B-BCU/UTP		5e	0,5	10	15	350x240x180	3,9
EC-PC4UD55B-BCU/UTP		5e	1,0	10	10	350x240x180	3,9
EC-PC4UD55B-BCU/UTP		5e	1,5	10	10	350x240x180	5,1
EC-PC4UD55B-BCU/UTP		5e	2,0	10	8	350x240x180	5,1
EC-PC4UD55B-BCU/UTP		5e	3,0	10	5	350x240x180	4,5
EC-PC4UD55B-BCU/UTP		5e	5,0	10	3	350x240x180	4,2
EC-PC4UD55B-BCU/UTP		5e	10,0	5	4	350x240x180	5,2
EC-PC4UD55B-BCU/UTP		5e	15,0	5	3	350x240x180	4,5
EC-PC4UD55B-BCU/UTP		5e	20,0	5	2	350x240x180	5,1

EC-PC4UD55B-BC-PVC-XXX-GY-yy

Patch cord Cat.5e, 4 pairs, stranded wire (7*0.16mm), PVC, Grey, 10 or 5 pcs/bag

Detailed characteristics

Characteristic	Value
Category	5e
Bandwidth, MHz	100
Construction	U/UTP
Number of twisted pairs	4
Conductors material	Bare copper
Conductors type	Stranded
Diameter of wire	26 AWG (7x0, 165±0,01)
Conductors insulation material	PE
Outer jacket material	5,5±0,03
Jacket color	Grey
Standard compliance	Meets the standards requirements: ISO/IEC 11801, EN 50173 and TIA/EIA-568
Application supporters	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive
Temperature ranges	Storage from -20 to +60. Installation from 0 to +50. Exploitation from -20 to +60
Package	PE package 10 pcs (group PE package include 10 or 5 individual PE packages)
Warranty	1 year
Connectors type	2xRJ45/8P8C
Wiring	T568B
Boot type	Molded
Jacket material	PVC