



EC-PC4UD55B-BC-PVC-XXX-GY-yy

Patch cord Cat.5e, 4 pairs, stranded wire (7*0.16mm), PVC, Grey, 10 or 5 pcs/bag

Таблица заказа

| P/N | Construction | Cat. | Length, m | QTY in group bag | | Transport box | Size, mm | Mass, kg |
|---------------------|--------------|------|-----------|------------------|-----|---------------|----------|----------|
| | | | | | QTY | | | |
| EC-PC4UD55B-BCU/UTP | | 5e | 0,3 | 10 | 20 | 350x240x180 | 4 | |
| EC-PC4UD55B-BCU/UTP | | 5e | 0,5 | 10 | 15 | 350x240x180 | 3,9 | |
| EC-PC4UD55B-BCU/UTP | | 5e | 1,0 | 10 | 10 | 350x240x180 | 3,9 | |
| EC-PC4UD55B-BCU/UTP | | 5e | 1,5 | 10 | 10 | 350x240x180 | 5,1 | |
| EC-PC4UD55B-BCU/UTP | | 5e | 2,0 | 10 | 8 | 350x240x180 | 5,1 | |
| EC-PC4UD55B-BCU/UTP | | 5e | 3,0 | 10 | 5 | 350x240x180 | 4,5 | |
| EC-PC4UD55B-BCU/UTP | | 5e | 5,0 | 10 | 3 | 350x240x180 | 4,2 | |
| EC-PC4UD55B-BCU/UTP | | 5e | 10,0 | 5 | 4 | 350x240x180 | 5,2 | |
| EC-PC4UD55B-BCU/UTP | | 5e | 15,0 | 5 | 3 | 350x240x180 | 4,5 | |
| EC-PC4UD55B-BCU/UTP | | 5e | 20,0 | 5 | 2 | 350x240x180 | 5,1 | |

EC-PC4UD55B-BC-PVC-XXX-GY-yy

Patch cord Cat.5e, 4 pairs, stranded wire (7*0.16mm), PVC, Grey, 10 or 5 pcs/bag

Детальные характеристики

| Характеристика | Значение |
|--------------------------------|--|
| Category | 5e |
| Bandwidth, MHz | 100 |
| Construction | U/UTP |
| Number of twisted pairs | 4 |
| Conductors material | Bare copper |
| Conductors type | Stranded |
| Diameter of wire | 26 AWG (7x0, 165±0,01) |
| Conductors insulation material | PE |
| Outer jacket material | 5,5±0,03 |
| Jacket color | Grey |
| Standard compliance | Meets the standards requirements: ISO/IEC 11801, EN 50173 and TIA/EIA-568 |
| Application supporters | 10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR-4, TR-16 Active, TR-16 Passive |
| Temperature ranges | Storage from -20 to +60. Installation from 0 to +50. Exploitation from -20 to +60 |
| Package | PE package 10 pcs (group PE package include 10 or 5 individual PE packages) |
| Warranty | 1 year |
| Connectors type | 2xRJ45/8P8C |
| Wiring | T568B |
| Boot type | Molded |
| Jacket material | PVC |