EC-URP-24-UE2

Patch Panel 19", 1U, 24 Ports, Cat.6 (Class E), 250MHz, RJ45/8P8C, Unshielded, Black



Таблица заказа

P/N	Cat.	Execution	Volume, m3	Weight, kg
EC-URP-24-UE2	6	Unshielded	0,002100	0,645

EC-URP-24-UE2

Patch Panel 19'', 1U, 24 Ports, Cat.6 (Class E), 250MHz, RJ45/8P8C, Unshielded, Black

Детальные характеристики

Характеристика	Значение
Category	6
Bandwidth, MHz	250
Execution	Unshielded
Number of ports	24
Height, U	1
Connectors type	RJ45/8P8C
Contact coating material	Gold, 3 microinches
Type of IDC contacts	110/KRONE
IDC coating material	Phosphorous bronze with nickel-plated coating
Permissible diameter of conductors, mm	0.511-0.404
Layout diagram	T568A/B
Plastic material	UL94V-0
Marking	All ports are numbered, there are additional marking areas
Installation	19'' Cabinet or rack
Material of the supporting structure	Steel 1.5 mm
Color	Black
Compliance	ISO/IEC 11801, EN 50173 и TIA/EIA-568
Supported Applications	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 2.5GBASE-T, 5GBASE-T,ATM-25,ATM-51,ATM-155, 100VG-AnyLan,TR4,TR-16 Active,TR-16 Passive
Temperature ranges	Storage -40 to +70 ° C. Installation 0 to +50 ° C. Operating 0 to +70 ° C
Warranty	1 year