

TLK-PPI-MN-A36B06-M61-WCE-BK

Elite Monitored PDU with Advanced network features, 400 VAC



Таблица заказа

P/N	Description	Volume, m3	Weight, kg
TLK-PPI-MN-A36B06-M61-WCE-BK	Elite Monitored PDU with Advanced network features	0.043659	8.500

TLK-PPI-MN-A36B06-M61-WCE-BK

Elite Monitored PDU with Advanced network features, 400 VAC

Детальные характеристики

Характеристика	Значение
Outlet	C13 - 36pcs., C19 - 6 pcs
Connection	IEC309, power cord, 3m
Overload Protection	16A UL489 breaker - 3pcs.
Ethernet Connection	1 x RJ-45
Sensor Connection	2 x RJ-11
Daisy Chain	2 x RJ-22
WiFi Ready	1 x USB
Info Display	Monochrome OLED
Output voltage	200-240 VAC
Output Max. Current	16 A, Per phase
Input voltage	400 VAC, 3 Phase 3P+N+PE
Input Max. Capacity	11 kVA
Frequency	50/60Hz, full range
Certification	CE
Temperature ranges	Storage -20 to +65 ° C. Operating 0 to +50 ° C.
Humidity ranges	Storage 0% to 95%. Operating 0% to 95%.
Net Size, mm	1778 x 56 x 80
Net Weight, kg	7.5
Warranty	1 year