

# TLK-PPI-SW-A14B02-M21-WCE-BK

Elite Switched PDU with Advanced network features, 240 VAC



## Ordering Table

P/N	Description	Volume, m3	Weight, kg
TLK-PPI-SW-A14B02-M21-WCE-BK	Elite Switched PDU with Advanced network features	0.031185	4.840

# TLK-PPI-SW-A14B02-M21-WCE-BK

Elite Switched PDU with Advanced network features, 240 VAC

## Detailed characteristics

Characteristic	Value
Outlet	C13 - 14pcs., C19 - 2 pcs
Connection	C20 inlet
Overload Protection	16A UL1077 breaker
Ethernet Connection	1 x RJ-45
Sensor Connection	1 x RJ-11
Daisy Chain	2 x RJ-22
WiFi Ready	1 x USB
Info Display	Monochrome OLED
Output voltage	200-240 VAC
Output Max. Current	16 A
Input voltage	200-240 VAC
Input Max. Capacity	3840 VA
Frequency	50/60Hz, full range
Certification	CE
Temperature ranges	Storage -20 to +65 ° C. Operating 0 to +50 ° C.
Humidity ranges	Storage 0% to 95%. Operating 0% to 95%.
Net Size, mm	1245 x 56 x 44
Net Weight, kg	4.2
Warranty	1 year