

TLK-RPI-MN-A08-M21-WCE-BK

Elite Monitored PDU with Advanced network features, 240 VAC



Таблица заказа

P/N	Description	Volume, m3	Weight, kg
TLK-RPI-MN-A08-M21-WCE-BK	Elite Monitored PDU with Advanced network features	0.009014	2.400

TLK-RPI-MN-A08-M21-WCE-BK

Elite Monitored PDU with Advanced network features, 240 VAC

Детальные характеристики

Характеристика	Значение
Outlet	8 x C13
Connection	C20 inlet
Overload Protection	16A UI1077 breaker
Ethernet Connection	1 x RJ-45
Sensor Connection	1 x RJ-11
DHCP Status	Green LED
SSL Status	Blue LED
Info Display	4 digits of 7 Segments
Output voltage	200-240 VAC
Output Max. Current	16 A
Input voltage	200-240 VAC
Input Max. Capacity	3840 VA
Frequency	50/60Hz, full range
Certification	CE
Temperature ranges	Storage -20 to +65 ° C. Operating 0 to +50 ° C.
Humidity ranges	Storage 0% to 95%. Operating 0% to 95%.
Net Size, mm	432 x 118 x 44.5
Net Weight, kg	2.1
Warranty	1 year