


EC-UU004-6-PVC-GY NETLAN cable, UTP 4 pairs, Cat.6, indoor, PVC, solid, 250MHz, 305m

- ✓ Applications on 5 Gbit/s speed
- ✓ Indoor

Four-pairs lan cable 6 category is used for organizing high-speed cable segments with data transfer rates up to 5 Gbit/s. Also it can be used for transmitting analog information.

Cable EC-UU004-6-PVC-GY have a 4 pairs twisted copper conductors, unshielded, corresponds to 6 category and is intended for indoor installation.

Shipped in cardboard boxes of 305 meters. For usability and transportation safety two individual boxes are merged in one transport cardboard box.



Marking*:
NETLAN EC-UU004-6-PVC-GY UTP SOLID ETHERNET LAN CABLE 4P
CATEGORY 6 PVC (Hr(B))

* Marking can be changed as the request of the customer

Basic equipment:
Cable

305m.



Manufacturer reserves the right to change external view and characteristics of product without reducing it's consumer properties

CHARACTERISTICS

P/N	EC-UU004-6-PVC-GY
Category	6
Bandwidth, MHz	250
Construction	U/UTP
Number of twisted pairs	4
Conductors material	Bare copper
Conductors type	Solid
Conductors diameter, mm	0.505±0.005
Conductors insulation material	HDPE
Conductors insulation thickness, mm	0.20±0.02
Conductors insulation outer diameter, mm	0.92±0.03
Outer jacket material	PVC
CPR Class	Eca
Usage	Indoor
Jacket thickness, mm	0.5±0.05
Jacket outer diameter, mm	5.8±0.2
Jacket color	Grey
Protective film	-
Separation	Yes, polyester
Rip cord	Yes
Mass density per unit lenght, kg/km	35.5
Bending radius without load, D	≥8
Bending radius with load, D	≥4
Tensile strength, H	≤80
Burst strength, H	≤400
Impedance, Ohm	100±15
Max. conductor resistance (DC), Ω/km	93
Standard compliance	Meets the standards requirements: ISO/IEC 11801, EN 50173 and TIA/EIA-568
Application supporters	10BASE-T, 100BASE-TX, 100BASE-T4, 1000BASE-T, 2.5GBASE-T, 5GBASE-T, ATM-25, ATM-51, ATM-155, 100VG-AnyLan, TR4, TR-16 Active, TR-16 Passive
Temperatures ranges °C	Storage from -20 to +60. Installation from 0 to +50. Exploitation from -20 to +60
Length, m	305
Package	Individual - cardboard box / transport cardboard box (2 individual boxes)
Package size (individual / transport, W x H x D), mm	205x390x390 / 430x410x410
Warranty	1 year

ORDERING TABLE

P/N	Category	Construction	Usage	Jacket color	Lenght, m	Volume, m3	Mass, kg
EC-UU004-6-PVC-GY	6	U/UTP	Indoor	Grey	305	0.033600	11.520